PC60 Silent X 300W Power Supply



The Shuttle XPC Accessory PC60 is the new version of Shuttle SFF power supply with compatibility of 300W. Power supply offers easy AC to DC switching. With low noise figure of 30dB, it fits in any noise-sensitive envi-

ronment like library and office. With an 80 PLUS efficient power supply standard, ENERGY STAR® qualified configurations, PC60 proves itself a saving in power consumption and energy costs.

FEATURES

- 300W Power Supply
- Compatibility G2/G5/G5M/G6/K/D Series
- Complies with Active PFC
- +5V Standby at 2.0A
- +3.3V Remote sensing
- Thermal Fan-speed control
- Energy Star V4.0
- Protection: OTP/OPP/UVP/OCP/SCP

SPECIFICATIONS

Model		PC60
Туре		300W SFF power supply
Input	Input range	90~264Vac
	Frequency	47~63 Hz
	Input current	6A/3A for 115V/230Vac
	Efficiency	Conform 80PLUS
	Inrush current	30A/60A for 115V/230Vac
Output	Hold up time	> 17ms at full load @115Vac
	Rise time	<20ms at full load, nominal line
	Short circuit protection	Latch Off
	Timing, Housekeeping and Control –REQUIRED	Conform Intel ATX12V Specific Guidelines 2.3
Environmental	Operating temperature	10°C to 50°C
	Storage temperature	-40°C to 70°C
	MTBF	>100,000 hrs at 75% load, 25°C ambient
	Noise	<30dB at 50cm for 200w Load
EMI/ RFI		FCC class B, CE, BSMI, CCC
SAFETY		cUL, TUV, CB, CCC
Dimensions	Size	190x82x43mm (LxWxH)
	Cable length	Cable lengths designed for the XPC
XPC compatibility		G2/G5/G5M/G6/K/D Series

Shuttle Inc.® 2008, All Rights Reserved.



^{*} All other brand and product names within this page are the property of their respective owners.

^{*} Specifications subject to change without prior notification.