

PN20 802.11b/g Wireless LAN Kit



FEATURES

Wicked-fast 54Mbps transfer rate up to 400 meters

Comply with 802.11b/g wireless standard

Equipped with External Antenna

Providing excellent wireless coverage

New OS Software compatibility

Windows 2000/XP/Vista, Linux

SPECIFICATIONS

Standard	Fully complies with IEEE 802.11 b/g specifications
Host Interface	USB 2.0
OS Compatibility	Windows 2000/XP/Vista, Linux
Frequency Band	2.4 ~ 2.484 GHz ((Industrial Scientific Medical Band)
Data Rate	802.11 b: DQPSK with data scrambling capability to provide data rate of 1, 2, 5.5, and 11Mbps 802.11 g: A high-speed Fast Fourier Transform (FFT) / Inverse Fast Fourier Transform (IFFT) provide data rate of 6, 9, 12, 18, 24, 36, 48 and 54Mbps
Operating Range	Indoors: 100m/Outdoors: 400m
Security	64/128-bit WEP/WPA—Wi-Fi Protected Access
Current Drain	Tx: 481.0mA/Rx: 319.9mA/Standby: 15.5mA
Operating Voltage	5 Volt ± 5%
Temperature Range	/0°C ~ 50°C (Operating)/-20°C ~ 80°C (Storage)
Humidity	0~90% Non-Condensing
Antenna Type	External, Designed for the XPC
Dimensions	78 x 20 x 4mm (l x w x d)
Weight	3g
XPC Compatibility	P series / G series Chassis



Shuttle Inc.® 2007, All Rights Reserved.

* All other brand and product names within this page are the property of their respective owners.

* The specification is subject to change without further notice.

We create!