

# »XPC ST20G5

## Technical Specs



### FEATURES

#### AMD ATHLON™ 64 (939) PROCESSORS

ATI RADEON XPRESS 200 + ULi 1573 chipset

#### INTEGRATED DIRECTX™9 AND OPENGL™

Play the latest games with sensational built-in graphics

#### SURROUNDVIEW™ TRIPLE DISPLAY SUPPORT

Integrate with a PCI-E x16 graphics card for amazing three display operation

#### SATA w/ RAID SUPPORT

SATA w/ RAID delivers faster data storage and retrieval whilst maintaining data integrity

#### SILENT X COOLING AND NOISE REDUCTION TECHNOLOGY

ICE heat-pipe module, Silent X 240W PSU, Active Airflow

## SPECIFICATIONS

### FORM FACTOR

- Shuttle Form Factor
- G5-series chassis

### PROCESSOR

- AMD Athlon™64/Athlon™64 FX Socket 939 CPU
- 1 GHz system bus with 2000MT/s Hyper-Transport link.

### CHIPSET

- North: ATi RADEON XPRESS 200
- South: ULi 1573

### ONBOARD VGA

- ATi RADEON XPRESS 200 graphics engine

### MEMORY

- (2) 184 pin 333/400 DDR DIMMs
- Dual-channel capable
- 2GB capacity, 1GB max per DIMM

### AUDIO

- Realtek ALC 880
- 7.1 Channel audio

### GIGABIT ETHERNET

- Broadcom 5751 (PCI-E)
- 10 Mb/s ,100 Mb/s and 1000Mb/s operation

### FireWire® 400

- VIA VT6307
- FireWire®400 OHCI v1.0 compliant
- Up to 400Mb/s data transfer rate

### SERIAL ATA RAID

- ULi 1573 integrated SATA
- Supports RAID 0,1, JBOD

### ONBOARD HEADER & CONNECTOR

- (1) ATA133 IDE connector
- (1) Floppy connector
- (3) Fan connectors
- (1) CD\_in header
- (1) Parallel port header
- (1) Wireless keyboard/mouse connector
- (2) SATA headers
- (1) Line\_in header
- (1) USB 2.0 2x5 header
- (2) USB 2.0 1x5 headers

### FRONT PANEL

- (1) Power button
- (1) Reset button
- (2) USB 2.0 ports
- (1) Mini FireWire port
- (1) Microphone
- (1) Speaker out

### BACK PANEL

- (1) PCI-E x16 slot
- (1) PCI slot
- (1) PS2 Keyboard/Mouse
- (1) VGA
- (1) DVI
- (2) USB 2.0 ports
- (1) FireWire port
- (1) RJ45 Gigabit LAN port
- (1) Rear-out
- (1) Front-out
- (1) Surr-out
- (1) Center/Bass
- (1) Fiber SPDIF\_in
- (1) Fiber SPDIF\_out
- (1) Clear CMOS

### EXTENSION BAY

- 2 x 3.5" bays
- 1 x 5.25" bay

### DIMENSION

- 200(W)x185(H)x310(L)

### POWER

- Output: 240 Watt
- Input: 100/240V AC
- Active PFC
- FCC/CE/BSMI/UL/TUV/CB certificated
- Power plug: Region Specific

### ACCESSORIES

- (1) Motherboard User manual
- (1) XPC Installation Guide
- (1) RAID User Guide / Floppy Driver
- (1) XPC Drivers CD
- (1) Shuttle Extras CD
- (1) ICE heat-pipe module
- (1) FDD Cable
- (1) HDD Cable
- (1) SATA Cable
- (1) Power cord
- Screws/Twin Adhesive/Front Feet

Shuttle Inc.® 2005, All Rights Reserved.

\* All other brand and product names within this page are the property of their respective owners.

\* The specification is subject to change without further notice.