

# »xpc SN21G5 *Versatile Mainstream Platform*



Mouse not included



## FEATURES

**AMD Athlon™ 64 / 64 FX / 64 X2 Processor**  
1GHz HyperTransport™ Technology  
Dual Channel DDR400

**NVIDIA® GeForce™ 6100 GPU**  
GeForce 6 Series Graphics Engine with PureVideo™  
PCI Express x16 Graphics Expansion

**NVIDIA nForce™ 410 MCP**  
NVIDIA RAID and MediaShield™  
Dual Channel SATA 3Gb/s Controller

**STEALTH DRIVE BAYS WITH ADVANCED I/O**  
FireWire® 400, USB 2.0, 10/100 LAN, 5.1 Channel Audio

**SILENT X COOLING AND NOISE REDUCTION**  
ICE heat-pipe, Silent X 250W PSU, Active Airflow

*We create!*

## SPECIFICATIONS

### FORM FACTOR

- Shuttle Form Factor
- G5 chassis

### PROCESSOR

- AMD Athlon™ 64 / 64 FX / 64 X2
- Socket 939

### CHIPSET

- NVIDIA® GeForce™ 6100
- NVIDIA nForce™ 410 MCP

### MEMORY

- 2 x 184pin DDR 333/400 DIMM
- Dual-Channel support
- Max 2GB capacity (1GB per slot)

### VGA

- GeForce 6100 GPU with PureVideo
- DirectX 9.0c, Shader Model 3.0
- MPEG2/WMV9 playback acceleration

### ATA

- SATA 3Gb/s interface with RAID 0,1
- ATA133 UltraDMA

### AUDIO

- Realtek ALC655 AC'97 audio
- 5.1 Channels / Coaxial output

### FAST ETHERNET

- Realtek 8201 Fast Ethernet PHY
- 10/100 Mb/s operation
- Power saving mode

### FIREWIRE® (IEEE1394a)

- VIA VT6307 controller
- IEEE1394 OHCI V1.0 compliant
- 400/200/100 Mb/s data transfer rate

### ONBOARD HEADERS & CONNECTORS

- (2) 4 pin fan connector
- (3) ATX Power connector
- (1) ATA133 UDMA IDE connector
- (2) Serial ATA connector
- (1) Front panel connector
- (1) 2x5 pin USB 2.0 header
- (2) 1x5 pin USB 2.0 header
- (1) Front Panel header
- (1) Parallel Port header
- (1) CD In connector
- (1) AUX In header
- (1) FDD connector
- (1) SPDIF In/Out connector

### FRONT PANEL

- (2) USB 2.0 port
- (1) Mini IEEE1394 port
- (1) Mic In
- (1) Earphone Out
- (1) Power on button
- (1) Reset button
- (1) HDD LED
- (1) Power LED

### BACK PANEL

- (1) PCI Express x16 slot
- (1) PCI slot
- (1) PS/2 Keyboard port
- (1) PS/2 Mouse port
- (2) USB 2.0 port
- (1) RJ45 10/100 Mb/s LAN port
- (1) IEEE1394a port
- (1) Front Out
- (1) Rear Out
- (1) Center/Bass Out
- (1) Coaxial Out
- (1) Line In
- (1) Clear CMOS button
- (1) VGA D-Sub port
- (1) COM port
- (1) Perforation for XPC Accessory PC8/PC9 (optional)
- (1) Perforation for XPC Accessory PN15g/PN18 (optional)

### EXTENSION BAY

- (1) 3.5" bay (external)
- (1) 3.5" bay (internal)
- (1) 5.25" bay

### DIMENSION

- 310(L) x 185(W) x 200(H) mm

### POWER

- SilentX 250W(PFC) Power Supply Unit
- 100-240VAC

### ACCESSORIES

- (1) User Guide
- (1) XPC Driver CD
- (1) Shuttle Extras CD
- (1) ICE Technology CPU heat-pipe
- (1) IDE cable
- (1) FDD cable
- (1) Power cord
- (1) SATA cable
- (1) FDD RAID disk
- (1) Screws pack

Shuttle Inc.® 2005, All Rights Reserved.

\* All other brand and product names within this page are the property of their respective owners.

\* The specification is subject to change without further notice.