

xpc SN25P

Technical Specs



*Optical Drive sold separately

FEATURES

AMD ATHLON™ 64 (939) PROCESSORS

2000MT/s system bus with HyperTransport™ link

NVIDIA® NFORCE™4 MCP CHIPSET

NVIDIA RAID, Gigabit Ethernet, Hardware Firewall

NVIDIA SATA/PATA RAID

Improve data integrity with multi-platform (SATA/PATA) RAID (0, 1, 0+1, JBOD)

SILENT X COOLING AND NOISE REDUCTION TECHNOLOGY

ICE heat-pipe module, Silent X350W PSU, Active Airflow

TOLLESS INSTALLATION

Toolless drive brackets and pre-installed thin, flat cables provide easy installation

SPECIFICATIONS

FORM FACTOR

- Shuttle Form Factor
- P-series chassis

PROCESSOR

- AMD Athlon™ 64/Athlon64 FX
- Socket 939 CPUs
- 1 GHz system bus with 2000MT/s Hyper-Transport link.

CHIPSET

- nForce™ 4 MCP

MEMORY

- (2) 184 pin 333/400 DDR DIMM slots
- 1GB per DIMM, max 2GB capacity
- Dual-channel memory controller

AUDIO

- 7.1 Channel H/W audio (VIA Envy24PT)

GIGABIT ETHERNET

- Marvell® Alaska® 88E1111
- 10 Mb/s, 100 Mb/s and 1000Mb/s operation

FIREWIRE® 400

- VIA VT6307
- 1394 OHCI v1.0 compliant
- Up to 400Mb/s data transfer rate

RAID SUPPORT

- Integrated NVIDIA SATA/PATA RAID
- Support RAID 0,1, 0+1, JBOD

ONBOARD HEADERS & CONNECTORS

- (1) ATA133 IDE connectors
- (1) Floppy connector
- (4) Fan connectors
- (1) CD_in header
- (1) Parallel port header
- (1) Wireless keyboard/mouse connector
- (4) SATA connectors
- (1) Line_in header
- (3) USB 2.0 headers
- (1) 8pin 12V power connector
- (1) 6 pin 12V power connector
- (1) IrDA header

FRONT PANEL

- (1) Power button
- (1) Reset button
- (2) USB 2.0 ports
- (1) FireWire port
- (1) Microphone
- (1) Headphones
- (1) 8-in-1 Card reader

BACK PANEL

- (1) PCI-E x16 slot
- (1) PCI-E x1 slot
- (1) PS2 Keyboard/Mouse
- (1) Serial Port
- (4) USB 2.0 ports
- (1) FireWire port
- (1) Gigabit (RJ-45) LAN port
- (1) Front /Center_out/Surr/Surr-back
- (1) Fiber SPDIF_in
- (1) Fiber SPDIF_out
- (1) Clear CMOS
- (1) Coaxial RCA connector
- (1) Line-in

EXTENSION BAY

- 1 x 3.5" bay
- 2 x 3.5" bays (Hidden)
- 1 x 5.25" bay

DIMENSIONS

- 220(W)x210(H)x325(L)

POWER

- Output: 350 Watt
- Input: 100/240V AC
- Active PFC
- Power plug: Region Specific

ACCESSORIES

- (1) Motherboard User manual
- (1) Motherboard CD-Driver
- (1) XPC Installation Guide
- (1) RAID User Guide / Floppy Driver
- (1) Shuttle extras CD
- (1) ICE heat-pipe module
- (1) FDD Cable
- (1) HDD Cable
- (1) SATA Cable
- (1) CD-ROM cable
- (1) Power cord
- Twin Adhesive/Front Feet/Drive brackets

Shuttle Inc.© 2002~2004, All Rights Reserved.

* All other brand and product names within this page are the property of their respective owners.

* The specification is subject to change without further notice.