

»xpc SN26P SLI ready SFF



Graphics cards and peripherals sold separately

FEATURES

AMD ATHLON™ 64/FX/X2 (939) PROCESSOR SUPPORT
2000MT/s system bus with HyperTransport™ link

NVIDIA® NFORCE™ 4 SLI CORE LOGIC
ActiveArmor™ secure networking engine, MetaShield™ SATA RAID, SATA 3Gb/s

PCI Express Scalable Link Interface
2 x16 PCI E slots support GeForce 7800 series graphics cards

SILENT X COOLING AND NOISE REDUCTION TECHNOLOGY
ICE heat-pipe module, Silent X 350W PSU, Active Airflow

TOOLLESS INSTALLATION
Toolless drive brackets and pre-installed thin, flat cables provide easy installation

SPECIFICATIONS

FORM FACTOR

- Shuttle Form Factor
- P series chassis

PROCESSOR

- AMD Athlon™ 64/FX/X2 Support
- Socket 939
- 1 GHz system bus with 2000MT/s Hyper-Transport link.

CHIPSET

- nForce™4 SLI

GRAPHICS

- (2) x16 PCI Express graphics slots

MEMORY

- (2) 184 pin 333/400 DDR DIMM slots
- 1GB per DIMM, max 2GB capacity
- Dual-channel memory controller

AUDIO

- VIA Envy24PT
- 7.1 Channel H/W audio
- Digital SPDIF I/O

GIGABIT ETHERNET

- Marvell PHY 88E1111
- 10/100/1000 Mb/s operation
- Supports Wake-on LAN

FIREWIRE® 400

- VIA VT6307
- Support 400Mb/s, 200Mb/s, 100Mb/s data transfer rate

RAID SUPPORT

- Integrated NVIDIA SATA/PATA RAID
- Support RAID 0,1, JBOD

ONBOARD HEADERS & CONNECTORS

- (1) ATA133 IDE connectors
- (1) Floppy connector
- (4) Fan connectors
- (1) CD-in header
- (1) Parallel port header
- (1) Wireless keyboard/mouse connector
- (4) SATA connectors
- (1) Line-in header
- (3) USB 2.0 headers
- (1) 8pin 12V power connector
- (1) 6 pin 12V power connector
- (1) IrDA header
- Clear CMOS jumper

FRONT PANEL

- (1) Power button
- (1) Reset button
- (2) USB 2.0 ports
- (1) FireWire port
- (1) Microphone
- (1) Headphones
- (1) 8-in-1 card reader

BACK PANEL

- (2) x16 PCI Express graphics slots
- (1) PS2 Keyboard/Mouse
- (1) Serial Port
- (4) USB 2.0 ports
- (1) FireWire port
- (1) Gigabit (RJ-45) LAN port
- (1) Front /Center- out/Surr/Surr-back
- (1) Line-in
- (1) Optical SPDIF-in/out
- (1) Coaxial RCA connector
- (1) Clear CMOS

EXTENSION BAY

- 2 x 3.5" bay (1 internal, 1 external)
- 1 x 5.25" bay

DIMENSIONS

- 325(L) x 220(W) x 210(H) mm

POWER

- Output: 350 Watt
- Input: 100/240V AC
- Active PFC
- EMI Certified: FCC, CE, BSMI
- Safety Certified: UL, TUV, CB
- Power plug: Region Specific

ACCESSORIES

- (1) User Guide
- (1) XPC Driver CD
- (1) Accessory Guide
- (1) RAID user manual
- (1) RAID floppy disk driver
- (1) Extras CD
- (1) ICE CPU heat-pipe Technology
- (1) FDD Cable
- (1) HDD Cable
- (1) Power Cord
- (1) SATA cable
- (1) Heatsink compound
- (1) SLI bridge card
- (1) Front Feet / Mounting brackets