

>xpc SB95P v2

Technical Specs



FEATURES

1066MHz INTEL® PENTIUM®4 LGA775 PROCESSORS

Intel 925XE + ICH6-R chipset

TOOLLESS DRIVE INSTALLATION

Revolutionary tool-free hard drive and optical drive installation

8-IN-1 CARD READER

Supports CF I, CF II, SD, MD, SM, MMC, MS, MSP

EASY INSTALL

Pre-installed thin, flat cables provide more space and easier installation

SILENT X COOLING AND NOISE REDUCTION TECHNOLOGY

ICE heat-pipe module, Silent X 350W PSU, Active Airflow

SPECIFICATIONS

FORM FACTOR

- Shuttle Form Factor
- P Chassis

PROCESSOR

- Intel® Pentium® 4 in the LGA775 pin package with 1066MHz FSB

CHIPSETS

- North Bridge: Intel 925XE
- South Bridge: ICH6-R

MEMORY

- (2) 240 pin 400/533 Dual Channel DDR 2 DIMMS (w/ECC)
- 2GB capacity and Max.1GB per DIMM

AUDIO

- Realtek ALC880 7.1 channel High Definition Audio

FAST ETHERNET

- Broadcom 5751 GBE (PCI-E x 1)
- 10/100 Mb/s LAN (operation)

IEEE 1394A

- VIA VT6307
- 1394 OHCI v1.0 compliant
- Up to 400Mb/s data transfer rate

SERIAL ATA RAID

- ICH6/R integrated SATA
- Dual Channel UDMA 150MB/s S-ATA
- Support RAID 0,1 (Intel Matrix Storage technology)

ONBOARD HEADER & CONNECTOR

- (4) Fan connectors
- (1) ATX main power connector
- (1) ATX 12V power connector
- (1) ATA 100 bus master IDE connector
- (4) Serial ATA connectors
- (1) Floppy connector
- (2) Front panel connectors
- (2) 1x5 pin USB 2.0 headers
- (1) 2x5 USB 2.0 header
- (1) Clear CMOS jumper

FRONT PANEL

- (1) Power button
- (1) Reset button
- (2) USB 2.0 ports
- (1) 8-in-1 card reader
- (1) IEEE 1394a port
- (1) Microphone
- (1) Earphone

BACK PANEL

- (1) PCI-Express x16 slot
- (1) PCI-Express x1 slot
- (1) PS2 Keyboard & Mouse port
- (2) USB 2.0 ports
- (1) IEEE 1394a port
- (1) Gigabit RJ45 LAN port
- (1) Rear / Front / Center & Bass_out / Surr_back
- (1) Line_In
- (1) Fiber SPDIF_in
- (1) Fiber SPDIF_out
- (1) Coaxial SPDIF_out
- (1) Clear CMOS
- (1) Serial port
- (1) WLAN Port (optional)

EXTENSION BAY

- 3 x 3.5" bays
- 1 x 5.25" bay

DIMENSION

- 220(W)x210(H)x325(L)

POWER

- 350W active PFC
- Input: 100 / 240V AC
- EMI Certified: FCC, CE, BSMI
- Safety Certified: UL, TUV, CB
- Power Cord: Plug dependant on region

ACCESSORIES

- Motherboard User manual
- Motherboard CD-Driver
- Shuttle Extras CD (PC-cillin, Acrobat reader 6.0, Muvee)
- XPC Installation Guide
- RAID User Guide
- ICE heat-pipe module
- FDD Cable
- SATA Cable
- FDD Power extension cord
- Power cord
- Twin Adhesive / Front Feet / Mounting bracket / Heatsink Compound

Shuttle Inc.® 2002~2004, All Rights Reserved.

* All other brand and product names within this page are the property of their respective owners.

* Specifications subject to change without further notice.