

»xpc SK22G2



FEATURES

AMD Sempron™/Athlon™ 64/Athlon™ 64 X2 (SOCKET AM2) SUPPORT
Optimized for productivity and multimedia applications

INTEGRATED COOLING ENGINE
New 92mm ICE heat-pipe module with advanced Smart Fan control

CABLE MANAGEMENT
Slim-line and pre-installed cabling removes airflow impedance and makes installation a snap

Supports AMD
Socket AM2
DDR2 Memory

ADVANCED CONNECTIVITY
Fully integrated audio/visual capabilities
Ethernet, SATA RAID, USB 2.0 and FireWire® 400

SPECIFICATIONS

FORM FACTOR

- Shuttle Form Factor
- Shuttle G2 Chassis

PROCESSOR

- AMD Sempron™/Athlon™ 64/Athlon™ 64 X2 processor
- Socket AM2
- Integrated DDR2 533/667/800 RAM controller

CHIPSETS

- North Bridge: VIA K8M890CE
- South Bridge: VT8237R+

MEMORY

- (2) 240pin DDR2 533/667/800
- Maximum up to 2GB per DIMM

VGA

- Integrated DeltaChrome 128bit 2D/3D
- DirectX 9.0 Compliant
- PCI Express x16 expansion slot

AUDIO

- Realtek ACL655
- 5.1 channel audio
- Digital SPDIF in/out support

FAST ETHERNET

- Fast 10/100 Ethernet
- Supports Wake-On-LAN function

STORAGE INTERFACE

- (2) 1.5Gb SATA
- (1) ATA UDMA 133
- RAID 0, 1, JBOD

IEEE1394 (FireWire®)

- VIA VT6307
- Support 400/200/100Mb/s transfer rate

POWER

- 200W active PFC
- Input: 110 / 240V AC
- EMI Certified: FCC, CE, BSMI
- Safety Certified: UL, TUV, CB
- Power Cord: region specific

DIMENSIONS

- 300(L) x 200(W) x 185(H) mm

EXPANSION BAY

- (1) 3.5" bay
- (1) 3.5" bay (Hidden)
- (1) 5.25" bay

ONBOARD CONNECTORS

- (2) 4 pin fan connector
- (1) ATX main power connector
- (1) ATX 12V main power connector
- (2) SATA connector
- (1) ATA133 bus master IDE connector
- (1) Floppy connector
- (1) 2x5 pin USB header
- (1) Line in header
- (1) Printer port header

FRONT PANEL

- (2) USB 2.0 port
- (1) Mini FireWire 400 port
- (1) Mic in
- (1) Earphone out
- (1) Power button
- (1) Reset button

BACK PANEL

- (1) PCI Express x16 slot
- (1) PCI slot
- (1) PS/2 Keyboard port
- (1) PS/2 Mouse port
- (1) Serial port
- (1) VGA port
- (4) USB 2.0 port
- (1) FireWire 400 port
- (1) RJ45 Ethernet port
- (1) Line in connector
- 5.1 Analog audio connectors
- (1) Clear CMOS button
- (1) Wireless hole for PN18(Optional)
- (1) Printer hole for PC8/9 (Optional)

ACCESSORIES

- (1) XPC user guide
- (1) Driver CD (32bit/64bit)
- (1) XPC Extras CD
- (1) Shuttle ICE Thermal Module
- (1) Power Cord
- (1) FDD Cable
- (1) IDE Cable
- (1) SATA Cable
- RAID driver floppy disks
- Screws
- Thermal compound



Shuttle Inc.® 2006, All Rights Reserved.

- * All other brand and product names within this page are the property of their respective owners.
- * The specification is subject to change without further notice.