

»xpc SS30G2



FEATURES

Intel® Celeron D/Pentium 4/Pentium D Processor Support

SiS 662 + 966L Chipset Supports Intel Single & Dual Core CPU

Single Channel DDR-II 667 Memory

PCI Express x16

Integrated Cooling Engine (ICE) Heat-pipe Module

Advanced Smart Fan Control

SPECIFICATIONS

FORM FACTOR

- Shuttle Form Factor
- Shuttle G2 Chassis

PROCESSOR

- Intel® CeleronD/Pentium 4/Pentium D processor
- Single & dual core CPU
- 533/800 MHz FSB
- LGA775 package

CHIPSETS

- North Bridge SiS 662
- South Bridge SiS 966L

MEMORY

- 2 x 240 pin DDR2 DIMM Socket
- 1GB per DIMM (Max 2GB)
- Single Channel Support

VGA

- SiS Mirage 1 Graphics
- High performance 256-bit 3D engine
- DirectX 7.0 complaint
- Max 128MB Shared Memory

AUDIO

- AC97 v2.3 compliant
- Support Analog 5.1 channel output
- Support Digital S/PDIF In/Out

FAST ETHERNET

- IEEE 802.3u 100Base-T compliant
- 10 Mb/s and 100 Mb/s operation
- Support Wake-on-LAN function

SATA

- SATA interface with RAID 0/1/JBOD
- NCQ support

IEEE1394 (FireWire®)

- Support 400/200/100Mb/s data transfer rate

POWER

- 200W PSU with active PFC
- Input 100 ~ 240V AC
- EMI Certified FCC, CE, BSMI, C-tick, CCC
- Safety Certified TUV, UL, CB, BSMI, CCC
- Power Plug Region Specific

DIMENSIONS

- 300(L) x 200(W) x 185(H) mm

EXPANSION BAY

- (1) 3.5" bay
- (1) 3.5" bay (Internal)
- (1) 5.25" bay

ONBOARD CONNECTORS

- (1) 3-pin fan connector
- (1) 4-pin fan connector
- (1) ATX main power connector
- (1) ATX12V power connector
- (2) SATA connector
- (1) UltraDMA133 Master IDE connector
- (1) Floppy connector
- (2) 1x5 pin USB header
- (1) Line in header
- (1) 6 pin S/PDIF Optical in/out header
- (1) Printer port header

FRONT PANEL

- (2) USB port
- (1) Mini FireWire 400 port
- (1) Mic in
- (1) Earphone out
- (1) Power button
- (1) Reset button

BACK PANEL

- (1) PCI Express x16 slot
- (1) PCI slot
- (1) PS/2 Keyboard port
- (1) PS/2 Mouse port
- (1) Serial port
- (1) VGA port
- (4) USB 2.0 port
- (1) FireWire 400 port
- (1) RJ45 Ethernet port
- (1) Line in connector
- 5.1 Analog audio connectors
- (1) Clear CMOS button
- (1) Wireless hole for PN18(Optional)
- (1) Printer hole for PC8/9 (Optional)

ACCESSORIES

- (1) XPC user guide
- (1) Driver CD (32bit/64bit)
- (1) XPC Extras CD
- (1) Shuttle ICE Thermal Module
- (1) Power Cord
- (1) FDD Cable
- (1) IDE Cable
- (1) SATA Cable
- RAID driver floppy disks
- Screws
- Thermal compound

Shuttle Inc.® 2006, All Rights Reserved.

* All other brand and product names within this page are the property of their respective owners.

* The specification is subject to change without further notice.