

»xpc ST22G2



FEATURES

AMD Sempron™ / Athlon™ 64 / Athlon™ 64 X2 (SOCKET AM2) SUPPORT
Optimized for productivity and multimedia applications

Support Windows Vista™ Premium

Support Dual Channel DDR2 533 / 667 / 800 Memory

Supports AMD
Socket AM2
DDR2 Memory

CABLE MANAGEMENT

Slim-line and pre-installed cabling removes airflow impedance and makes installation a snap

SPECIFICATIONS

FORM FACTOR

- Shuttle Form Factor
- Shuttle G2 Chassis

PROCESSOR

- AMD Sempron™ / Athlon™ 64 / Athlon™ 64 X2 processor
- Integrated DDR2 533/667/800 RAM controller

CHIPSETS

- North Bridge AMD 690G
- South Bridge AMD SB600

MEMORY

- 2GB per Slot (Max. 4GB)
- Support DualDDR2 533/667/800

VGA

- Integrates an ATI Radeon X1250-based graphics engine
- DirectX 9.0 complaint

AUDIO

- Realtek ALC888
- 7.1 Analog Channel output
- Support Digital S/PDIF in/out

FAST ETHERNET

- Realtek 8110SC
- 10/100/1000Mb/s operation

STORAGE INTERFACE

- (2) 3.0Gb SATA, support RAID 0, 1
- (1) Ultra DMA 133 IDE channel

IEEE1394 (FireWire®)

- VIA VT6308P
- Support 400/200/100Mb/s transfer rate

POWER

- 250W active PFC
- Input: 100 / 240V AC
- EMI Certified: FCC, CE, BSMI, CCC
- Safety Certified: UL, TUV, CB, CCC
- Power Cord: region specific

DIMENSIONS

- 300(L) x 200(W) x 185(H) mm

EXPANSION BAY

- (1) 3.5" bay
- (1) 3.5" bay (Hidden)
- (1) 5.25" bay

ONBOARD CONNECTORS

- (1) 4 pin fan connector
- (1) 3 pin fan connector
- (1) ATX main power connector
- (1) ATX 12V main power connector
- (3) SATA connector
- (1) ATA133 bus master IDE connector
- (1) Floppy connector
- (2) 1x5 pin USB header
- (1) AUX in header
- (1) Printer port header
- (1) Front penal header

FRONT PANEL

- (2) USB 2.0 port
- (1) Mini FireWire 400 port
- (1) Mic in
- (1) Earphone out
- (1) Power-On button
- (1) Reset button

BACK PANEL

- (1) PCI Express x16 slot
- (1) PCI slot
- (1) Serial port
- (1) DVI-I port
- (6) USB 2.0 ports
- (1) FireWire 400 port
- (1) RJ45 Ethernet port
- (1) eSATA port
- (1) Line in connector
- (1) Clear CMOS button
- (1) Front out connector
- (1) Side surround out connector
- (1) Rear surround out connector
- (1) Center / Bass connector
- (1) Wireless hole for PN18(Optional)
- (1) Printer hole for PC8/9 (Optional)
- (1) Optical S/PDIF In / out (Optional)

ACCESSORIES

- (1) Multilanguage Quick User Guide
- (1) Driver CD (32bit/64bit)
- (1) XPC Extras CD
- (1) Shuttle ICE Thermal Module
- (1) Power Cord
- (1) FDD Cable
- (1) IDE Cable
- (1) SATA Cable
- RAID driver floppy disks
- Screws
- Thermal compound



Shuttle Inc.® 2006, All Rights Reserved.

- * All other brand and product names within this page are the property of their respective owners.
- * The specification is subject to change without further notice.