



SN41G2 V2

Hot Feature Highlight

400 FSB ready

The first VGA integrated XPC to support the 400 / 333 / 266 / 200 FSB AMD Athlon XP / Duron processors.

AMD Athlon XP Burn Proof

With AMD Athlon XP Burn Proof technology, the system will automatically protect processor from damage due to over heat.

High Performance built in GeForce 4 MX Graphics Engine

The highest performance of built in graphics engine in AMD platform

nView

Allows user to work different processes with 2 monitors simultaneous

Smart Fan Control

Auto Fan speed control makes the lowest noise

NVIDIA nForce 2 IGP based XPC

I.C.E. Heat-Pipe

High performance and efficient to make CPU and system work in stable environment temperature.



Specification

Form Factor

- Shuttle Form Factor

Processor

- AMD Athlon XP / Duron in the 462 pin package with 200/266/333/400MHz FSB

Chipsets

- NVIDIA nForce2 IGP + MCP-T

Memory

- Two x 184 pin dual channel 200/266/333 DDR SDRAM DIMM slots support up to 2GB memory

Audio

- On board Realtek ALC650 6-channel audio

Fast Ethernet

- Support NVIDIA Fast Ethernet with 10/100Mbps operation

1394a

- Support NVIDIA 1394 with data transfer rates up to 100,200, and 400 Mbits/s

Front Panel

- 2 x USB connectors
- 1 x mini 1394a
- 1 x Mic-In, 1 x Earphone, 1 x Line in
- 1 x Power-On button with indicator
- 1 x Reset button with indicator

On board header

- 1 set of 2x5 pin USB header
- CD Audio_In header
- SPDIF_In / Out header
- Parallel port header

On board connectors and jumpers

- 3 x Fan connectors
- 1 x ATX main power connector
- 1 x ATX 12V power connector

- 2 x UltraDMA133 Master IDE connector
- 1 x Floppy connector
- Clear CMOS

Back panel

- 1 x PCI / 1 x AGP (8X mode) slot
- 1 x PS/2 Keyboard / Mouse
- 2 x USB2.0 ports
- 1 x Serial port
- 1 x RJ45 port
- 2 x IEEE1394a ports
- 1x Rear out, 1x Front out, 1x Center/Bass
- 2 x VGA ports / 1 x TV out
- 1 SPDIF In / Out

Extension Bay

- 2 x 3.5" bays 1 x 5.25" bay

Dimension

- 300(L) x 200(W) x 185(H) mm, 2.85Kg (N.W.), 4.65Kg (G.W.)

Material

- Aluminum

Power

- Input: 100 - 240V AC
- Output: 250W(PFC)
- EMI Certified: FCC, CE, BSMI, CCC
- Safty Certified: UL, TUV, CB, CCC

Accessories

- 1 x Mainboard User manual
- 1 x Mainboard CD-Driver
- 1 x XPC Installation Guide
- 1 x I.C.E Technology CPU heat-pipe
- 1 x set of cable (FDD / HDD /ATAPI)
- 1 x Power cord
- Screws, Twin Adhesive, Friendly Front Feet