

PC22 22-in-1 Card Reader



FEATURES

- High Speed USB 2.0 interface - up to 480Mb/sec
- Mass storage driver support
- No additional drivers needed under Windows 2000/XP or later
- Standard 3.5" drive bay installation
- 3 changeable color panels - black, white and silver
- Active LED indicators - power, read/write activity
- USB bus powered - no external power required
- Supports direct card to card transfers
- Supports 22 card formats

SPECIFICATIONS

Model	PC22	
Type	22-in-1 card reader	
Sockets	MS, CF Type I/II, SD/MMC, SM	
Supported card formats*	CompactFlash Type I (CFI), CompactFlash Type II (CFII), CompactFlash Ultra II, Microdrive (MD), SmartMedia (SM), Memory Stick (MS), Memory Stick Duo, Memory Stick PRO, Memory Stick PRO Duo, Memory Stick MagicGate (MSMG), Memory Stick MG Duo, Memory Stick MG PRO, Memory Stick MG PRO Duo, High Speed Memory Stick (HSMS), Secure Digital (SD), Mini Secure Digital (MiniSD), Secure Digital Ultra, MultiMediaCard (MMC), MultiMediaCard II, High Speed MultiMediaCard (HS-MMC), Reduced Size MultiMediaCard (RS-MMC), TransFlash (TF)	
Available colors	Black, white and silver (changeable front panel)	
Operating System support	Windows 2000/XP or later	
Interface	Internal USB 2.0 (USB 1.1 backward compatible)	
Power	+5V DC (powered directly from USB)	
Environmental	Operating Temperature	0°C ~ +70°C
	Storage Temperature	-40°C ~ +70°C
	Operating Relative Humidity	50%
	Storage Relative Humidity	95% (Max without condensing)
	MTBF	>10,000 insertion cycles
Size	3.5" drive bay installation	
Package contents	22-in-1 card reader, 3 changeable front panels, 2 cables (1x5 pin USB header, 2x5 pin USB header)	

*adaptor required for some formats



Shuttle Inc.© 2005, All Rights Reserved

* All other brand and product names within this page are the property of their respective owners

* Specifications subject to change without prior notification

We create!