

PN18 802.11b/g Wireless LAN Kit

Technical Specs



FEATURES

Wicked-fast 54Mbps transfer rate up to 400 meters
Wireless 802.11b/g standard

Industry-standard security built-in
64/128/256 bits WEP, WPA Encryption

Share your internet with friends and family
Free Shuttle Access Point Software Utility bundled

Designed for the XPC
P, L, i, G, G2, G4, G5-series XPCs

SPECIFICATIONS

Standard	WiFi IEEE802.11g Compliant
Host Interface	USB 2.0
OS compatibility	Windows 98SE/ME/2000/XP, Linux
Frequency band	2.400 ~ 2.4835GHz (Subject to Local Regulations)
Data rate	1Mbps, 2Mbps, 5.5Mbps, 6Mbps, 9Mbps, 11Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Operating range	up to 400 meters (open space)
Security	64/128/256 bit WEP Encryption 802.1x, WPA (Windows XP SP1/SP2 and Windows 2000 SP4 only)
Current drain	Tx: 350mA Rx: 250mA Standby: 10mA
Operating voltage	5 Volt \pm 5%
Temperature range	0°C ~ 65°C (Operating) -20°C ~ 70°C (Storage)
Humidity	95% Non-Condensing (MAX)
Antenna Type	External, Designed for the XPC
Dimensions	74 x 23 x 7.4mm (l x w x d)
Weight	5g
XPC compatibility	P, L, i, G, G2, G4, G5-series XPCs
Shuttle Access Point Software	WEP / WPA Encryption MAC Address Filtering MS Internet Connection Firewall

Shuttle Inc.© 2005, All Rights Reserved.

* All other brand and product names within this page are the property of their respective owners.

* Specifications subject to change without prior notification.

