

XPC SB51G



Form Factor

Shuttle Form Factor

CPU Support

Intel Pentium 4/Celeron in 478-pin package with 400/533MHz FSB, Support **Hyper Threading** Processor

Chipsets

Intel 845G/ICH4

Memory

2 x 184 pin Socket support DDR200/266/333 unbuffer DDR SDRAM up to 2GB

VGA

Build in Intel 845G high performance 256-bit 3D engine

Audio

Realtek ALC 650 supports 5.1 channel audio
Support Digital SPDIF In/Out

IDE interface

2 x UltraDMA/100 IDE channels

IEEE 1394a

VIA VT6306, complies with 1394 OHCI specification revision 1.0 support up to 400Mb/s data transfer rate

Ethernet

Realtek 8100B support IEEE 802.3u 10/100Base-T
Supports Wake-On-LAN function

Expansion Slot

1 x 4x mode AGP slot
1 x PCI slot

OnBoard connectors and Headers

3 x fan connectors
1 x ATX main power connector
1 x Peripheral power connector
2 sets of 2x5 pin USB2.0 heads
1 set of 2x5 pin Front Panel IEEE1394a header
1 set of Parallel header
CD_In header
Mic_In header
Speaker_Out header
SPDIF_Out header

Chassis

Shuttle G type

Dimension

300(L)x200(W)x185(H)mm, 2.85Kg (N.W.), 4.65Kg (G.W.)

Material

Aluminum

Extension Bay

2 x 3.5" bays 1 x 5.25" bay

Front Panel

2 x USB ports 1 x 1394 port
1 x SPDIF-Out 1 x Mic-In
1 x Speaker-Out 1x Power-On button
1x Reset button

Back Panel

1 x PCI slot 1 x AGP slot
1 x PS/2 Keyboard 1 x PS/2 Mouse
1 x VGA port 2 x Serial Port
2 x 1394 ports 1 x SPDIF In
2 x USB ports 1 x RJ45 port
1 x Front out connector 1 x Rear out connector
1 x Center/Bass port 1 x Parallel port (optional)

Power

Dimension: 82(W) x 43(H) x 190(D) mm (Max)
Input: 110 / 230V AC
Output: 200W(PFC)
EMI Certified: FCC, CE, BSMI
Safty Certified: UL, TUV, CB
Power Cord: Depends on specific region demand

Accessories

1 x Mainboard User manual
1 x Mainboard CD-Driver
1 x XPC Installation Guide
1 x I.C.E Technology CPU heat-pipe
1 x FDD Cable
1 x HDD Cable
1 x CD-ROM Cable
1 x Power cord
Screws
Twin Adhesive
Friendly Front Feet