



SiS650/961 based XPC

SS50G

Hot Feature Highlight

Processor

Intel Pentium 4/Celeron in 478-pin package with 400MHz FSB

AGP 8X

Support high performance and 533MHz high bandwidth AGP 8X mode

CPU Temp.

Auto Fan speed control makes the lowest noise

I.C.E. Heat-Pipe

High performance and efficient to make CPU and system work in stable environment temperature.

Specification

Form Factor

- Shuttle Form Factor
- CPU Support
- Intel Pentium 4/Celeron in 478-pin package with 400MHz FSB

Chipsets

- SiS650/961
- Memory
- 2 x 184 pin Socket support DDR200/266 unbuffer DDR SDRAM
- up to 2GB

VGA

- Build in SiS315 high performance 256-bit 3D engine
- TV-Out
- SiS301 support NTSC and PAL format in S-Video/Composite ports

Audio

- Cmedia 8738 supports 5.1 channel audio
- Support Digital SPDIF In/Out
- IDE interface
- 2 x UltraDMA/100 IDE channels
- IEEE 1394a
- Lucent FW323, complies with 1394 OHCI specification revision
- 1.0 support up to 400Mb/s data transfer rate

Ethernet

- Realtek 8100B support IEEE 802.3u 10/100Base-T
- Supports Wake-On-LAN function
- Expansion Slot
- 2 x PCI slots
- On board connectors and Headers
- 3 x fan connectors
- 1 x ATX main power connector
- 1 x Peripheral power connector
- 2 sets of 2x5 pin USB2.0 headers
- 1 set of 2x5 pin Front Panel IEEE1394a header
- 1 set of Parallel header
- CD_In header
- Mic_In header
- Speaker_Out header
- SPDIF_Out header

Chassis

- Shuttle C type
- Dimension
- 280(L)x200(W)x180(H)mm, 2.70Kg (N.W.), 4.20Kg (G.W.)

Material

- Aluminum
- Extension Bay
- 2 x 3.5" bays 1 x 5.25" bay
- Front Panel
- 2 x USB ports 1 x 1394 port
- 1 x Mic-In 1 x Speaker-Out
- 1 x Power-On button 1 x Reset button
- Back Panel
- 2 x PCI slots 1 x PS/2 Keyboard
- 1 x PS/2 Mouse 1 x VGA port
- 2 x Serial ports 2 x 1394 ports
- 2 x USB ports 1 x RJ45 port
- 1 x Front out connector 1 x Rear out connector
- 1 x Center/Bass port 1 x S-video/composite port

Power

- Dimension: 82(W) x 43(H) x 190(D) mm (Max)
- Input: 110 / 230V AC
- Output: 160W/150W(PFC)
- EMI Certified: FCC, CE, BSMI
- Safty Certified: UL, TUV, CB
- Power Cord: Depends on specific region demand

Accessories

- 1 x Mainboard User manual
- 1 x Mainboard CD-Driver
- 1 x XPC Installation Guide
- 1 x FDD Cable
- 1 x HDD Cable
- 1 x CD-ROM Cable
- 1 x 7pin Mini DIN to RCA Cable
- 1 x Power cord
- Screws
- Twin Adhesive