

## »xpc SD30G2



### FEATURES

Intel® Core 2 Duo series with 1066MHz FSB Processor  
Intel® Pentium D with 800MHz FSB Processor  
Intel® Celeron with 533MHz FSB Processor

Intel® 945GC + ICH7 Chipset

DDR2 533/667 Memory, 1GB per DIMM (Max 2GB)

Build in a Intel® GMA950 256bit 3D engine

#### CABLE MANAGEMENT

Slim-line and pre-installed cabling removes airflow impedance and makes installation a snap

## SPECIFICATIONS

### FORM FACTOR

- Shuttle Form Factor
- Shuttle G2 Chassis

### PROCESSOR

- Intel® Core 2 Duo series, Pentium D Celeron Processor
- 533 / 800 / 1066MHz FSB
- LGA775 package

### CHIPSET

- North Bridge Intel® 945GC
- South Bridge ICH7

### MEMORY

- 2 x 240 pin DDR2 533/667MHz DIMM Slots
- 1GB per DIMM (Max 2GB)
- Support Dual channel

### VGA

- Build-in Intel® 945GC
- Intel® Graphics Media Accelerator GMA 950 (Intel® GMA 950)

### AUDIO

- Realtek ALC888
- Support Analog 7.1 channel output
- Support Digital S/PDIF in/out

### FAST ETHERNET

- Marvell 88E8056 (PCI-E Interface)
- IEEE 802.3u 1000Base-T compliant
- 10Mb/s . 100Mb/s and 1000Mb/s operation

### STORAGE INTERFACE

- (1) UltraDMA 100 IDE channel connector
- (2) On board SATA3.0Gb/s connector
- (1) Floppy connector

### POWER

- 250W PSU with PFC
- Input 100 - 240V AC
- EMI Certified FCC, CE, CCC
- Safety Certified TUV, UL, CB, CCC, CSA, NEMKO
- Power Plug region specific

### DIMENSIONS

- 300(L) x 200(W) x 185(H) mm

### EXPANSION BAY

- (1) 3.5" bay
- (1) 3.5" bay (Hidden)
- (1) 5.25" bay

### ONBOARD CONNECTORS

- (2) 4 pin fan connector
- (1) ATX main power connector
- (1) ATX 12V main power connector
- (2) SATA connector
- (1) ATA100 bus master IDE connector
- (1) Floppy connector
- (2) 1x5 pin USB header
- (1) AUX in header
- (1) CD\_In header
- (1) Optical S/PDIF header
- (1) Printer port header
- (1) Front panel header

### FRONT PANEL

- (2) USB 2.0 ports
- (1) mini IEEE1394
- (1) Mic in
- (1) Earphone out
- (1) Power-on button
- (1) Reset button
- (1) Power indicator - blue
- (1) HDD indicator - orange

### BACK PANEL

- (1) PCI Express x16 slot
- (1) PCI slot
- (4) USB 2.0 ports
- (1) RJ45 Gigabit Ethernet port
- (1) Line in connector
- (1) Front out connector
- (1) Rear surround connector
- (1) Side surround connector
- (1) Center/Bass connector
- (1) D-sub port
- (1) IEEE 1394 port
- (1) PS/2 keyboard port
- (1) PS/2 mouse port
- (1) Clear CMOS button
- (1) Fiber S/PDIF out connector
- (1) Wireless hole for PN18 (Optional)
- (1) Printer hole for PC8/9 (Optional)

### ACCESSORIES

- XPC Multilanguage Quick User Guide
- XPC CD Driver (XP and Vista 32/64 bit)
- Shuttle Extras CD
- (1) Power cord
- (1) IDE cable (pre-install)
- (1) SATA cable (pre-install)
- (1) Floppy cable
- Screws
- Thermal compound



Shuttle Inc.® 2007, All Rights Reserved.

- \* All other brand and product names within this page are the property of their respective owners.
- \* The specification is subject to change without further notice.