

PN18g 802.11b/g Wireless LAN Kit



FEATURES

Wicked-fast 54Mbps transfer rate up to 400 meters

Wireless 802.11b/g standard

Industry-standard security built-in

64/128/256 bits WEP, WPA Encryption

Share your internet with friends and family

Free Shuttle Access Point Software Utility bundled

Designed for the XPC

P, L, i, G, G2, G4, G5-series XPCs

SPECIFICATIONS



Standard	WiFi IEEE802.11g Compliant
Host Interface	Standard USB2.0 Interface
OS compatibility	Windows 98 SE/ ME / 2000 / XP / Linux / Vista
Frequency band	2.400 ~ 2.4835 GHz (subject to Local Regulations)
Data rate	1 Mbps, 2Mbps, 5.5Mbps, 6Mbps, 9 Mbps, 11 Mbps, 12 Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Operating range	up to 400 meters (open space)
Security	64/128/256 bit WEP Encryption, WPA Encryption
Current drain	Tx: 350mA
	Rx: 250mA
	Standby: 10mA
Operating Voltage	5 Volt
Temperature range	Operating : 0° C ~ 60° C
	Storage : -20° C ~ 70° C
Humidity	Max. 95% non-condensing
Antenna Type	External, Designed for the XPC
Dimensions	74(W) x 23 (L) x 7.4 (H) mm
Weight	5g
XPC compatibility	P, P2, L, i, G, G2, G5 series XPCs
Shuttle Access Point Software	WEP / WPA Encryption
	MAC Address Filtering
	MS internet Connection firewall
Shuttle Inc.® 2007, All Rights Reserved.	
* All other brand and product names within this page are the property of their respective owners.	
* Specifications subject to change without prior notification.	